Notebook, N-09-03-24

			25	
Dup 8415	8418	667	970	
21% KOH, 2 gram $LiOH$ –	8419	697	980	
	8420	1027	1160	
Edison 41 Conc $NiCl_2$ soak 7/9 –	8421	917	980	
1 gram Cond + boil KOH, dip 3 of 2 wires	8422	913	990	
broke up –	8423	830	907	
21% KOH.				
Dup 8421	8424	1027	1147	
21% 2 $LiOH$ –	8425	1010	1130	
	8426	1007	1123	
Edison 38 Rd 7/9	8427	1023	970	
Orthophenol – Bad – 1 soak	8428	1050	990	
Conductance 21% KOH, 4.5 f 1/2 23.7	8429	1057	983	
Dup 8427	8430	926	513	
21% 2 $LiOH$ –	8431	590	467	
	8432	597	—	
Edison 43 Nickelphenol, Bad	8433	646	1063	
one soak 7/9 Rd –	8434	593	1053	
4.2 1/2 f 24.2	8435	593	1050	
7/9				
Dup 8433	8436	943	1077	
21% KOH – 2 gram $LiOH$.	8437	913	1067	
	8438	917	1027	
Edison 44 Sod. KSO_4 – one	8439	1210	1220	
soak 1 f 1/2 4.4 – 23.8 gram	8440	1207	1217	
7/9 Rd 21% KOH – 6.24	8441	1217	1220	

Dup 8439	8442	1127	1237
21% KOH, 2 gms LiOH.	8443	1130	1257
	8444	1133	1267
Elem 45 Conc Stammite Bact single-streak 42 23.9.	8445	1273	1213
	8446	1277	1210
21% KOH.	8447	1290	1217
Dup 8445	8448	1147	1283
21% KOH, 2 gms LiOH.	8449	1150	1257
	8450	1133	1283
Elem Conc Antimonite Phase Bact- one-streak -	8451	767	843
	8452	770	847
21% KOH.	8453	760	840
Dup 8451	8454	727	1017
21% KOH, 2 gms LiOH —	8455	740	1027
	8456	767	1083
Rep Tube 4.4 % f: 24.4 green 719 Ra- 3 or 4 grams Bismuth Nitrate in candle -	8457	1177	1357
	8458	1173	1297
21% 2 LiOH —	8459	1173	1287
green mod — 8081- 4.2 % f 24 green-	8460		1350
27% KOH 2 gms LiOH —	8461		1380
	8462		1370
719 Ra Bismuth nitrate Rep % f 4 % f 24 green the Control Grade with Antimonite KOH-manganese dioxide 1st Rep 619 - 21% KOH.	8463	1243	1167
	8464	1220	1107
Dup 8463 - 21% KOH 2 gms LiOH.	8465	1210	
	8466		

25

3 | 1273 / 1258

2 | 97 / 1240

9 | 3127 / 1042

8481 starts with 103 flocks
unwashed 1/2 thick squares OX
+ Reduced by Zn++ by 25 re pumping

Dup 8463	8466	1197	1337
21% KOH 2 rpm at 60°	8467		
	8468		
Reg Exam 1½ 3½ 237	8469	1227	1200
½ sq f ox - heated 10	8470	1210	1178
½ sq f ox - heated 10 min in 0.5 N HCl	8471	1200	1160
21% KOH.			
Dup 8469	8472	1220	1347
21% KOH 2 rpm LiOH -	8473	1210	1367
	8474	1220	1333
Dup 8469	8475	1187	1123
Except flocks treated HCl -	8476	1183	1150
8 sheets 10 rpm ft 1000 cc H2O	8477	1200	1193
21% KOH.			
Dup 8475	8478	1200	1323
21% KOH. 2 rpm LiOH.	8479	1197	1280
Zn++ on flocks	8480	1207	1323
Reg Exam 1½ 3½ 237 6.39	8481	1217	1170
Sep f ½ ox 6 flocks unwashed Dearborn	8482	1220	1137
Zinc Hydroxide Gel - 5 rpm KOH,	8483	1207	1137
Stirred - very little ppt - 1 drop			
1 drop + each direction no change in			
21% KOH 2 hours 4:15			
Dup 8481 flocks about same	8484	1200	1267
21K 2 LiOH	8485	1207	1257
6.39	8486	1200	1267

Acid treatment of flocks
removes Al_2O_3 & Fe_2O_3

Dup 8481 except tube stuck welded 2 min Hydrogen 719 2 hour 21K	8487	1157	1150	
	8488	1153	1107	
	8489			
Dup 8487 21K 2 Lioth.	8490	1183	1293	
	8491	1167	1287	
	8492			
Reg Tubes No 3 Ft 43 2 1/2 719 2 hour — about 10 drops Nitric acid 21K	8493	1200	1150	
	8494	1217	1150	
	8495	1200	1110	
Dup 8493 21K 2 Lioth.	8496	1200	1257	
	8497	1193	1277	
	8498	1213	1277	
Dup 8493 But some amount flake 16 drops Nitric 21K	8499	1217	1157	
	8500	1200	1150	
	8501	1200	1157	
Dup 8499 21K 2 Lioth.	8502	1190	1273	
	8503	1193	1300	
	8504	1183	1257	
Reg Tubes 4,4 1/2 2 mesh Ruska 719 RQ 720 1/2 w filters Adsorbent 21K	8505	1180	1170	
	8506	1173	1160	
Dup 8505 21K 2 Lioth.	8507			
	8508	1173	1333	
Dup 8505 21% K 2 Lioth.	8509	1187	1343	
	8510			

Dup 8505	8511	1297	1230
24 ½ KOH 6 gm Li OH	8512	1330	
	8513	1280	
Reg latter RQ721 Zinc & filtered-dried Zinc hydr-fallowed in latter prep books like yest-not taken 7th 4.4 g ½ wet basis 6.77	8514	1213	1218
	8515	12	1227
	8516		1213
Dup 8514	8517		
21K 2 Li OH.	8518		
	8519		
Take whole washed Zinc Hydrogen 719 RQ 2 hours	8520		
21K	8521		
	8522		
Dup 8520	8523		
21K 2 Li OH,	8524		
	8525		
Dup 8520 first time 4 g whole has not been ignited Grey colour Some Grit up in Hydrogen Zn —	8526	Too fine	Too fine
	8527	Colour	Colour too
	8528		
	8529		
	8530		
	8531		
Dup 8520 Take whole washed Zn Hydr. heat RQ 720 time 4.4 ½ g gm not 24.3	8532		
	8533		
	8534		

Dup 8532	8535
21K 2 Lobes.	8536
	8537
Dup 8520 Continue RA 721 filtered, in fully grown tube which received 2nd H. 4.4 ½ peak	8538
	8539
21K	8540
Dup 8538	8541
21K 2 Lobes.	8542
	8543
Dupe of 8337 Req Tube 4.4 ½ .24 gm	8544
	8545
	8546
Req Tube no 103 F ½ second of 721 Req Unmasked by Stratification ½ w filtered, Low heat 6.47	8547
	8548
	8549
Dup 8547	8550
21K 2 Lobes.	8551
	8552
Req Tube RA 721 ½ W filtered, corrected Density in 4.4 ½ f peak. Light color Like 708 6.35	8553
	8554
	8555
Dup 8533	8556
21K 2 Lobes.	8557
	8558

Carfin 1338–

Bifurcated Tube – 1313

Bastogne Hyd middle on path – 1331

Hyde Farm Sidy – 1320

Bridge – Electricity 1338

" 1 Tr " 1322

" Yew Berry " 1332

" 2m " 1293

Sidy 1305

Nr Sidy – 1303

Farm Hse – 1337

" 5 Hses 1373

" 5 Hse 1368

Sidy – 1342

Bn Cross – 1340

Intersect on Hyde 1293 – 1335

Trig 2 ——— 1334

" 4 " 1330

2/2456
1293

36 mile 600 daily ±

6000

216000

[ITEM FOUND IN BOOK]



Flake

9 = on Twirling goes to powder — its very moist on face — rolls up Easy — hard to get off to Twirl Slippery appears lumpy in it — lots dandruff

1 A the highest from wheel Badly making all the ox + rosolic Explo before Explg — Shiny — hard to Twirl don't break up handily dry.

Ex No 1 OX black readers Yz Hy — pure — now more moist but not so much as No 3 — Easily gathered together for Twirling don't break up much —

19 + 20 too slippery to Twirl —

35 = Hard to Twirl don't break up much.

24 Not quite so hard to twirl as 35 —

[ITEM FOUND IN BOOK]


21 K 5 gms LiCl – Burette for plate
two tube burst
2 "
1 "
1 sphtscum
1 bottom sphit –
1 burst
1 "
CO2 ok K Silicate 2 gms with or without
LiOH very bad – Phthalein Hydroxy
Exceedingly bad on Brew –
RA 718 very good acc 8172. Req 21 as
good – 21 LiOH –
719 rather good with Req 21 but Eglin
good with LiOH – + Bismuth –
Phos in presence LiOH very bad
720 good acc 8509

[ITEM FOUND IN BOOK]



[ITEM FOUND IN BOOK]



1 A ot 6lk unpumped —

800 Tab

1 Hour 1274 D
2 hours 1251
4 hours 1274 D 1270

700 Tab

1 Hour 1266
2 " 1288 D
4 " 1233 1267

1000 Tab

1 Hour 1240
2 " 1283 D
4 " 1246 1256

Outlet to H20 wash only

2 hours 1298
4 " 1277

Inlet leaks H20 wash only

2 hours 1257 - 1223
4 hours 1269 - 1240

[ITEM FOUND IN BOOK]



			1150	
725A,	7354	6.21	1218	1.96
" B	7422	6.32	1305	206
" C	7551	6.48	1341	208
D	7669	6.52	1329	204
E	7813	6.64	1322	200
F	8069	6.82	1358	198
SG	6432	5.47	1114	203
X	8127	6.92	1331	192
SH.	7266	6.18	1236	200
SJ	7429	6.32	1277	202
SL	7368	6.32	1250	198
1088A	7164	6.10	1347	221
1086 B	8041	6.85	1378	201
1088 C	7009	5.97	1290	216
1088 D	7963	6.77	1352	200
1089 G	6034	5.14	1030	200
25 SM	74477	6.35	1332	210
Y	8100	6.90	1393	200

[ITEM FOUND IN BOOK]



[ITEM FOUND IN BOOK]



[ITEM FOUND IN BOOK]



	Cold	50 Hot	100 Hot	150 Hot
9357		283	693	670
9381	1125	300	585	599
9385	1133	433	416	
9421	1171	415	423	
9429	1000	315		
9433	1223	381	583	
9445	1238	340	570	
9502	1156	571	540	
9623	1200	526		
9641	1094	428		
9660	1136	451		
9662	1135	420		
9674	1092	441		
9674	1090	455		
9676	1110	345		
9698	1156	368		
9706	1151	368		
9709	1064	352		
10231				
10235				
10239				

[ITEM FOUND IN BOOK]

Mr. Edison -

Do I understand from your wire that all those will have to be tested 150 but runs before it can be used in the large cells, or am I to go ahead and make No O.K. for Rodgers the same way as I made # 719 - 2 hrs. gets 50 hot runs, and if O.K. use in the large cells?

Had I not better go ahead and make one batch every week (350 lbs) and get tests on it so when Rodgers is ready I will be ready, and then we will be not behind at this end?

I will make one batch every week to duplicate #719 - 2 hrs until we find something better and then we can do so.

Kindly let me know about this by return mail so I can get started at once for it takes a long time to get tests. (4 weeks for each 50)

K-A.

West Orange, N.J.
March 9, 09.

Mr. Edison.

Dear Sir:-

The following tubes went up to Hooper. #1014A. Dup. of #9710 Except throw 30 on 190 mesh, and Lot 104 Stock 20A Ni flake.

Flake 42 Green 24.0 #1 Machine.

2.7 KOH + 2 gms LiOH. Run Regular.

37E dump out 7.773

1015A. 240 " wt 7.805

1016A. Dup. of #9716 Except throw 30 on 190 mesh, and Lot 104 Stock 20A Ni flake.

Flake 42 Green 24.0 #1 Machine.

2.6 KOH + 2 gms LiOH. Run Regular.

264 dump out 7.122

1017A. 263 " wt 7.132

1018A. Dup. of #9722 Except throw 30 on 190 mesh and Lot 104 Stock 20A Ni flake.

Flake 4.2 Green 23.9 #1 Machine.
21% KOH + 2. gms LiOH. Run Regular.
261 dumpers wt 7.196
1019A. 260 " wt 7219
1020A. Disp. of #9728 Except 1 box 30 pcs. 190 meals, and Lot 104 Stock 20 Aim flake.
Flake 4.2 Green 23.9 #1 Machine.
21% KOH + 2. gms LiOH. Run Regular.
282 dumpers wt 7.750
1021A. 278 " wt 7.744

The following are some of the loading weights of Prbogacta green's that have below 7.000 gms per tube.

Rd #1182	Green 23.8	flake 4.2	dumpers 24	wt 6.069	
" " 1189	" 23.8	" 4.2	" 231	" 6282	
" " 1191	" 23.7	" 4.2	" 243	" 6370	
" " 1192	" 23.7	" 4.2	" 229	" 5.943	
" " 1194	" 23.8	" 4.2	" 253	" 6.640	
" " 1195	" 23.8	" 4.2	" 235	" 6415	

[ITEM FOUND IN BOOK]

RQ
1196 lbs Eg for screen 23.7 Flake 4.2 dumper 233 wt 6.128
" 1198 " " " 23.8 " 4.2 " 238 wt 6.954
There are a couple of more to make up which I will send to-morrow.

Yours Respectfully
Walter Wheeler

P.S. I told John Watt about fixing up the rolls so I could get rid of the fines through 19 mesh.

[ITEM FOUND IN BOOK]

2/4/09.

Here are results on two, similar, old-bonded cells, - one having 100 grams of SiO_2H in the 21% HO_2H, and the other having the regular 120 grams.

Cells were run like #404, results of which I have sent you, - that is, they were given three overcharge runs and then run on commercial charges, as if in service.

RUN	CHARGE	DISCHG.	#467		#466		
			To IV.	To 0.50	To IV.	To 0.50	
			100g SiO_2H		120g SiO_2H		- in 21% HO_2H.
1	48 hrs. @ 15	Oct 30	222.5	234	215	231.5	Cells contain:
2	15 hrs. @ 30	"	180.5	190	165	194.5	735 $Ni(OH)_2$ 164 Lahe
	Allowed to stand 46 hours						
3	15 hrs. @ 30	Oct 30	178	191.5	165	196.7	I think these results
	Allowed to stand 36 hours						give evidence that it
4	7 hrs. @ 30	Oct 30	152.5	—	150	—	is advisable to use
5	"	"	161.5	—	160.7	—	less SiO_2H. The 120-
6	"	"	162.5	—	162.5	—	gram cell has more
7	"	"	164.2	—	163.5	—	reserve capacity
8	"	"	164	—	161.2	—	below IV. and event-
9	"	"	167	—	166.	—	ually it will prob-
10	"	"	168	—	166.5	—	ably have a capac-
11	"	"	166.2	—	166	—	ity to IV. 10 ampere-
12	"	"	167.7	—	167.5	—	hours or so better
13	"	"	169.2	—	169.3	—	than the 100-gram
14	"	"	168	—	168	—	cell; but these col-
15	"	"	169.5	192	170	198.5	ourtages are slight
16	15 hrs. @ 30	"	173.5	204.5	176	218.7	compared with the
17	7 hrs. @ 30	"	163.7	—	168.2	—	better durability
18	"	"	171.2	—	175.8	—	which, I believe, the
19	"	"	172.5	—	175.5	—	100-gram cell will
20	"	"	172	—	175	—	have. W.E.H.

[ITEM FOUND IN BOOK]

March 4, 1909.

Mr. Edison:

Below are the first three runs of three cells containing the new-loaded tubes. These cells contain different amounts of SiO_2H in 21% KOH, but this makes little difference in their capacities at the start. It is the same with the old cells. These new cells, however, are starting out a little lower than the average cell of the old loading. I did not have any old cells of the same 7 tube and Hydrate which is in these, and that may account for the difference. Anyway it is the ultimate and not the first capacity which counts.

New-loaded cells #478, 479, + 480, contain:

#478 – 739 $Ni(OH)_2$, 29 Zn + 203 Cu + 7 tube, 90 grams SiO_2H

479 – " " " 105 grams SiO_2H

480 – " " " 120 grams SiO_2H

Run	Charge	Discha.	#478		#479		#480	
			To 1 V.	To .50	To 1 V.	To .50	To 1 V.	To .50
1	48 hrs. @ 15	Ot 30	210.7	220.7	207	221.2	202.5	219.7
2	15 hrs. @ 30	"	178.5	187.2	168.5	185.7	169.2	185.2
3	"	"	173.5	183.7	165	183.7	170	185.5

Walter E. Holland

[ITEM FOUND IN BOOK]

March 6, 1909.

Mr. Edison:

On December 4th we put six "A4" cells in series, in a Thomas-Co. truck – as you will remember. A few days ago they completed 1000 miles (taking 12 weeks time), and I had them taken out for test. Here are the results on the last run before, and on four runs after, the series in truck:

Run	Charge	Dis.	#231	#232	#376	#380	#387	#390
Before	15 hrs@30	01 30	203	209.5	196	207.5	212.5	207.5
	9th truck 12 weeks;				run	1000	miles	
After	15 hrs@30	01 30	228.5	231.5	229.5	231	237.5	232
"	"	"	192.5	194.5	197.5	198	204.5	208
"	"	"	195	197	199	202	206	210
"	"	"	192.7	194	197.5	201.5	205	210.5

Cells #231 + 232 contain #728 $Ni(OH)_2$ and #247 Cobalt
Others contain #731 $Ni(OH)_2$ and 10+20 % Cobalt.

These cells were used in the beginning for various experiments as to forming. They were variously treated as follows:

#231 + 232.

Originally in 21 % KOH + 15 g. SiO4 per cell. After 3 runs, saturated SiO4 solution was put in. Cells were run 28 times in this and 21 % KOH was then substituted. Cells had altogether 44 runs before being put in trucks.

#376.

Original electrolyte – 21 % KOH + 120 g. SiO4 Had 20 overcharge runs during which new electrolyte of 21 % KOH was put in.

*380.

Electrolyte – 21 g. KOH + 120 g. SiO_2. Had 16 normal overcharge runs and was reversed once at 15 amperes for 30 hours. Solution has never been changed.

*387.

Electrolyte – 21 g. KOH + 120 g. SiO_2. Had 15 normal overcharge runs. Solution has never been changed.

*390.

Original electrolyte – 21 g. KOH + 60 g. SiO_2. Had 19 normal overcharge runs during which the solution was changed three times – fresh electrolyte of the same kind being put in each time.

Have got two more runs on the new-loaded cells. They are now on their upward course. Here are all the runs:

RUN	CHARGE	DIS.	*478 To 1V.	*478 To .5V.	*479 To 1V.	*479 To .5V.	*480 To 1V.	*480 To .5V.
			90 g. SiO_2		105 g. SiO_2		120 g. SiO_2	
1	48 hrs. @ 15	Oct. 30	210.7	220.7	209	221.2	202.5	219.7
2	15 hrs. @ 30	"	178.5	197.2	168.5	185.7	169.2	185.2
3	"	"	173.5	183.7	165	183.7	170	185.5
4	"	"	178.5	189	170	190.5	175	192.2
5	"	"	178.5	190	173.5	191	178.5	196.5

Walter E. Holland

[ITEM FOUND IN BOOK]

March 10, 1909.

Mr. Edison:

Here are the runs to date of the three new-loaded cells:

Run	Charge	Disch'g	#478 To 1V.	#478 To 0.50	#479 To 1V.	#479 To 0.50	#480 To 1V.	#480 To 0.50
			90 p. Soft		105 p. Soft		120 p. Soft	
1	48 Km. @ 15	Oct 30	210.7	220.7	207	221.2	202.5	219.7
2	15 Km. @ 30	"	178.5	187.2	168.5	185.7	169.2	185.2
3	"	"	173.5	183.7	165	183.7	170	185.5
4	"	"	178.5	189	170	190.5	175	192.2
5	"	"	178.5	190	173.5	191	178.5	196.5
	Allowed cells to stand 5 hours.							
6	15 Km. @ 30	Oct 30	187.2	200	180	202	183	204.2
7	"	"	182	191.2	178.2	194.3	182.5	199
8	"	"	181	190	174.5	193	182.7	199.2

The two-day rest did not seem to help them much. Shall try them on short charge now.

We now have six more of the new cells; will send results on them as soon as I can get results.

We had a little cold weather last week and I got several cold tests on A4 cells. A cold discharge affects the output very considerably, while a cold charge (down to 40° F.) is not at all bad. I have curves on this which you can see when you return.

Walter E. Holland

[ITEM FOUND IN BOOK]

March 16, 1909.

Mr. Edison:

I think it would be well to try the effect of various catalytic substances on the charging-curve of iron as you suggest, but I do not think we should put the Fe es up with Bismuth-Nickel tubes: that would be introducing too many unknown factors. Moreover, I don't see why we should not eliminate the Nickel factor altogether: it can be done, as I have demonstrated, by assembling the Fe es with inactive electrodes of pure nickel and using an external source of current to both charge and discharge. The volt-readings on discharge of course are negative, but they are constant; and the method gives the true and unadulterated curve of the iron both on charge and on discharge.

If you think favorably of this plan I will have the cells made up and you can send the list of chemicals at your convenience.

Respectfully yours
Walter S. Holland

[ITEM FOUND IN BOOK]

March 17, 1909.

Mr. Edison:

I gave 3 of the new-loaded cells the treatment with 8 % KOH + 120 g. SiO_2, - changed to 25 % KOH after 3 runs; but this time I varied the treatment a little and discharged at 60 amperes on the 2nd and 3rd runs. You will notice that the output at this high rate is very low; but it heats the cells, with resultant benefit. There are better on the 5th run than old-loaded cells treated in the same way (except in the matter mentioned of high rate discharge).

Run	Charge	Disch'g	#481		#482		#483	
			To 1V.	To .50	To 1V.	To .50	To 1V.	To .50
	Original Electrolyte - 8 % KOH + 120 g. SiO_2.							
1	48 hrs. @ 15	Dt 30	140	169	147	175.7	151.7	190.2
2	15 hrs @ 30	Dt 60	—	96	—	98.5	—	120
3	"	"	—	44.5	—	47.5	—	99
	Set stand 32 hours; then put in 25 % KOH							
4	15 hrs @ 30	Dt 30	166.5	190.7	168	190	168	186.7
5	"	"	170.5	190.7	172	191.2	172	189

The 3 original new-loaded cells I have been giving commercial runs, to form them; and they show up very well on these runs. They are running in series, and as we have no convenient way to cut them out at 1V., they get completely discharged each time, - therefore the efficiency should be figured from the results to .50 V.

Following are the results:

Run	Charge	Discha	#478 To 1V.	#478 To 50	#479 To 1V.	#479 To 50	#480 To 1V.	#480 To 50	
			90 g.		105 g.		120 g.		= 5.0% in 21 g. NOH.
9	7 hrs @ 30	Oct 30	160.2	165.7	161.2	169.2	165.2	175.7	Runs #1-8 were
10	"	"	161.7	166.5	163.2	171.5	166.5	176.5	overcharge tests.
11	"	"	161.2	165.5	161.7	171	166.7	176.7	I sent them to you
12	"	"	160	166	162.5	171.5	165	179.5	last week.
13	"	Oct 60	137	165	130	172.5	131.5	180	
14	"	"	136.5	164	130	168	130	178	
15	"	"	136.5	164	126	169	128	177	
16	"	"	140	167	133	173	134	180	
17	"	Oct 30	162	167.5	163	172.5	167	180.5	
18	"	"	161	165	162	170	165	178.7	

A4 Cell #404 (old-loaded), has been run under approximately commercial conditions for a long time, to find the rate of improvement. Here is a condensation of the results:

Charge and discharge rate: 30 amperes.

Runs #1-3	Overcharge tests	3rd run	= 167.5 to 1V.
" 4-15	7 hour charges	Average	164.2 "
" 16	15 hour charge	—	189 "
" 17	"	—	197 "
" 18-29	7 hour charges	Average	171.9 "
" 30	15 hour charge	—	199.7 "
" 31-42	7 hour charges	Average	174.6 "
" 43	15 hour charge	—	205 "
" 44-45	7 hour charges	Average	178.8 "

The electrolyte is 21 g. NOH + 120 g. SiO2H2.

W.E.A.

[ITEM FOUND IN BOOK]

March 24, 1909.

Mr. Edison:

A4 cells #478 – 480 (new-loaded) are gone 16 commercial runs after the first overcharge runs, – here are the results on over-charge after these commercial runs:

Run	Charge	Dis.	#478 To 1V	#478 To 0.8V	#479 To 1V	#479 To 0.8V	#480 To 1V	#480 To 0.8V
25	15 km.@30	Ot 30	204.2	212	200	217.5	201.5	222
26	"	"	198.5	209.5	194.7	214.7	200	220

As you know, #478 has 90 g. LiOH, #479 has 105 g, and #480 has 120 g. – in 21 g. KOH.

Here are results on new A4 cells #484 – 486, which contain #739 $Ni(OH)_2$, 25 Zn + 203 Bn + 1 Lake, and are filled with 21 g. KOH + 120 g. LiOH, –

Run.	Charge	Dis.	#484 To 1V	#484 To 0.8V	#485 To 1V	#485 To 0.8V	#486 To 1V	#486 To 0.8V
1.	48 km. @ 15	Ot 30	200	219	201.7	220.2	200	219.7
	Allowed to stand				24 hours.			
2	15 km@30	Ot 60	114	192	120	193.	120	190.7
	Allowed to stand				12 hours			
3	15 km@30	Ot 60	110	191.5	114	192.5	110.5	191.5
	Allowed to stand				64 hours.			
4	15 km@30	Ot 30	175	204.7	177.5	206.7	177.5	202.6
5	"	"	173.5	199	175	198.5	173.5	194.5

Results on new A4 cells #487 – 489.

Run	Charge	Dis.	#487 To 1V	#487 To 0.8V	#488 To 1V	#488 To 0.8V	#489 To 1V	#489 To 0.8V	These cells are
1	48 km@15	Ot 30	193	212.7	193	212.2	193	212.7	exactly same
	Allowed to stand				24 hours				as #484-486 –
2	15 km@30	Ot 60	111	194.5	111	192	111	194.5	have except that
	Allowed to stand				12 hours				they contain
3	15 km@30	Ot 60	110	185	111	184.7	111	184.7	#0 #1 Lake.
	Allowed to stand				64 hours				
4	15 km@30	Ot 30	170	198.2	170	196	172.5	197.5	W.E.M.
5	"	"	169	190	168.5	193.5	170	199	

[ITEM FOUND IN BOOK]

Long Tubes- (32)

Coll	H.R.	H.R. @ 250	1	2	3	
10262	350	1000	1838	1754	1688 - 2067	
10263		950	1904	1854	1792 - 2121	
* 10264		858	1679	1675	1608 - 2004	Helix.
10277		842	1958	1913	1842 2163	
10278		808	1675	1808	1763 - 2146	
10279		771	1704	1675	1617 - 1971	
10280		875	1771	1750	1708 - 2071	
10281		867	1779	1750	1688 - 2017	
10282		780	1658	1654	1583 - 1842	
10286	200	729	1675	1633	1558 - 1850	
10287		761	1721	1708	1692 - 1992	
10288		742	1742	1738	1696 - 1942	
10308	150	688	1867	1863	1833 - 1938	
10309		688	1604	1768	1758 - 1888	
10310		683	1375	1733	1813 - 2004	
10311		638	1825	1829	1808 - 1892	
10312		688	1771	1771	1738 - 1833	
10313		617	1783	1792	1742 - 1854	
10340	46	504	1638	1763	1742 - 1783	
10341		396	1704	1835	1758 - 1846	

MAR 25 1909 MAR 26 1909 MAR 27 1909

Mr. Edison:

New-bonded A4 cells #484-489, we gave five regular forming-runs at the start, then twelve commercial runs, = charging 7 hrs. at 20 amps. and discharging at 40 amps. Here are results on two overcharge runs made after the commercial runs:

Cell #484	Run #18 – 199 to 1V., 208 to 50	Run #19 – 199.5 to 1V., 209.5 to 50V.
" 485	" 199 " 205.5 "	" 199 " 204.5 "
" 486	" 198.5 " 203 "	" 199 " 203 "
" 487	" 193 " 198.5 "	" 194 " 198.2 "
" 488	" 190 " 195 "	" 190 " 195.5 "
" 489	" 193 " 198.2 "	" 194 " 198.2 "

#484-486 have #739 $Ni(OH)_2$ and #28 XH + 203 BH 7 holes

#487-489 " " " " " #0 7 holes

Electrolyte in all is 21 o/o KOH + 120 g. LiOH.

New-bonded A4 cells #481-483, containing #739 $Ni(OH)_2$ and #28 XH + 203 BH 7 holes, had an electrolyte of 8 o/o KOH + 120 g. LiOH for 3 runs, and then were filled with 25 o/o KOH. They then had 3 more overcharge runs and 18 commercial runs, after which their capacity on overcharge was as follows:

Cell #481	Run #25 – 199.2 to 1V., 205 to 50V.	Run #26 – 197.2 to 1V., 205.5 to 50V.
" 482	" 190 " 206.2 "	" 193.2 " 207.5 "
" 483	" 198.5 " 203.5 "	" 191.5 " 204 "

[ITEM FOUND IN BOOK]

Here are summaries of tests on some old A4 cells which had no forming treatment, but were simply given runs under commercial conditions, (approximately), with an overcharge every 12 runs:

A4 #466 + #467

#466 - Electrolyte: 21 % KOH + 120 g. SiO_2.

#467 - " " " 100 g. SiO_2.

Both contain #735 $Ni(OH)_2$ and #16A Flake

Runs	Charge	Disch.	#466	#467	Remarks
#3	15 hrs. @ 30	0.t 30	165.0 to 1.V.	179.0 to 1.V.	
4-15	7 hrs. @ 30	"	165.4 "	166.1 "	Average (12 runs)
16	15 hrs. @ 30	"	194.0 "	193.5 "	
17-28	7 hrs. @ 30	"	175.3 "	171.9 "	Average
29	15 hrs. @ 30	"	206.7 "	203.5 "	
30-41	7 hrs. @ 30	"	177.5 "	174.0 "	Average
42	15 hrs. @ 30	"	211.2 "	206.0 "	

A4 #468.

Electrolyte: 9 % KOH + 120 g. SiO_2 for 3 runs, then 25 % KOH. #735 $Ni(OH)_2$ and #16A Flake.

Runs	Charge	Disch.	#468	Remarks
#5	15 hrs. @ 30	0.t 30	171.0 to 1.V.	
6-17	7 hrs. @ 30	"	165.4 "	Average
18	15 hrs. @ 30	"	192.5 "	
19-30	7 hrs. @ 30	"	170.2 "	Average
31	15 hrs. @ 30	"	202.5 "	
32-43	7 hrs. @ 30	"	171.3 "	Average
44	15 hrs. @ 30	"	201.5 "	

[ITEM FOUND IN BOOK]

Just before you went away you told me about running some hot-discharge experiments, on small cells which had lost capacity. We have now finished the tests, - here are the results:

T.A.E. Tube Cells #158, 161, & 164.

Electrolyte: 21 g. KOH + 2g. SiO_2.

Run	Charge	Discharge	Discharge Temp	#158	#161	#164	
166	15 hrs. @ 300	Ot 200	Norm. (75°)	920	903	1013	
167-170	" "	"	130° F.	1219	1190	1347	Average
171-175	30 hrs. @ 150	"	"	1351	1300	1383	"
176-178	" "	"	115° F.	1233	1183	1307	"
179-181	" "	"	100° F.	1110	1053	1203	"
182-183	" "	"	Norm. (75°)	933	927	1000	"
184-186	15 hrs @ 300	"	"	927	920	990	"

I have been doing considerable work for the Primary Battery Company. Am designing a new cell which ought to be a winner. It will have two zinc plates and three oxides, with potash or silicate electrolyte. The internal resistance will be half that of the present cell, and the amount of zinc surface, which the electrolyte can act on, will be double.

Walter E. Holland

April 3, 1909.

[ITEM FOUND IN BOOK]